



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** ALUMINUM EXTRUSIONS, ANODIZED ALUMINUM PRODUCTS

**Other means of identification**

**SDS number** 509

**Version #** 06

**Revision date** May 27, 2015.

**Other means of identification**

**Synonyms** Aluminum Alloys 6xxx Series

**Recommended use** Fabricated aluminum parts and products

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

Alcoa Inc.  
201 Isabella Street  
Pittsburgh, PA 15212-5858 USA  
Health and Safety Tel: 1-412-553-4649  
Health and Safety Fax: 1-412-553-4822  
Health and Safety Email: accmsds@alcoa.com

**Emergency Information** CHEMTREC: +1-703-527-3887 +1-800-424-9300 (24 Hour Emergency Telephone, multiple languages spoken); ALCOA: +1-412-553-4001 (24 Hour Emergency Telephone, only English spoken)

**Website** For a current Safety Data Sheet, refer to Alcoa websites: [www.alcoa.com](http://www.alcoa.com) or internally at [my.alcoa.com](http://my.alcoa.com) EHS Community

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Not classified.

**Environmental hazards** Not classified.

**Authority defined hazards** Combustible dust

**Label elements**

**Hazard symbol** None.

**Signal word** Warning

**Hazard statement** May form combustible dust concentrations in air.

**Precautionary statement**

**Prevention** Prevent dust accumulation to minimize explosion hazard.

**Response** Not assigned.

**Storage** Not assigned.

**Disposal** Reuse or recycle material whenever possible.

**Hazard(s) not otherwise classified (HNOC)** None known.

## Supplemental information

Dust and fume from processing: Can cause irritation of the eyes, skin and respiratory tract. Additional health effects from elevated temperature processing (e.g., welding, melting): Acute overexposure: Can cause metal fume fever, reduced ability of the blood to carry oxygen and the accumulation of fluid in the lungs.

Non-combustible as supplied. Small chips, fine turnings and dust from processing may be readily ignitable.

Explosion/fire hazards may be present when:

- Dust or fines are dispersed in air.
- Chips, dust or fines are in contact with water.
- Dust and fines are in contact with certain metal oxides (e.g., rust, copper oxide).
- Molten metal is in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide).

## 3. Composition/information on ingredients

**Composition comments** Complete composition is provided below and may include some components classified as non-hazardous.

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminum		7429-90-5	96 - 99
Zinc		7440-66-6	<6.5
Manganese		7439-96-5	<1.5
Magnesium		7439-95-4	<1.2
Chromium		7440-47-3	<0.35

**Additional Information** Exact composition will vary. Unless additional information is available, processor should assume that all potential ingredients are present. Additional compounds which may be formed during processing are listed in Section 8.

## 4. First-aid measures

### Eye contact

Dust and fumes from processing: Rinse eyes with plenty of water or saline for at least 15 minutes. Consult a physician.

### Skin contact

Dust and fumes from processing: Wash with soap and water for at least 15 minutes. Get medical attention if irritation develops or persists.

### Inhalation

Dust and fumes from processing: Remove to fresh air. Check for clear airway, breathing, and presence of pulse. Provide cardiopulmonary resuscitation for persons without pulse or respirations. If breathing is difficult, provide oxygen. Loosen any tight clothing on neck or chest. Consult a physician.

### Ingestion

Not relevant, due to the form of the product.

### Most important symptoms/effects, acute and delayed

Dust and fumes from processing: Can cause irritation of the eyes, skin and upper respiratory tract. See Section 11 of the SDS for additional information on health hazards.

### Medical conditions aggravated by exposure

Dust and fume from processing: Asthma, chronic lung disease, Secondary Parkinson's disease and skin rashes.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

### Suitable extinguishing media

Use Class D extinguishing agents on fines, dust or molten metal. Use water spray to cool exposed containers.

### Unsuitable extinguishing media

DO NOT USE halogenated extinguishing agents on small chips/fines. DO NOT USE water in fighting fires around molten metal. These fire extinguishing agents will react with the burning material.

<b>Specific hazards arising from the chemical</b>	<p>May be a potential hazard under the following conditions:</p> <ul style="list-style-type: none"> <li>• Dust clouds may be explosive. Even a minor dust cloud can explode violently. Dust accumulation on the floor, ledges and beams can present a risk of ignition, flame propagation and secondary explosions.</li> <li>• Chips, fines and dust in contact with water can generate flammable/explosive hydrogen gas. These gases could present an explosion hazard in confined or poorly ventilated spaces.</li> <li>• Dust and fines in contact with certain metal oxides (e.g., rust, copper oxide). A thermite reaction, with considerable heat generation, can be initiated by a weak ignition source.</li> <li>• Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide). Moisture entrapped by molten metal can be explosive. Contact of molten aluminum with certain metal oxides can initiate a thermite reaction. Finely divided metals (e.g., powders or wire) may have enough surface oxide to produce thermite reactions/explosions.</li> </ul>
<b>Special protective equipment and precautions for firefighters</b>	Firefighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing when appropriate.
<b>General fire hazards</b>	This product does not present fire or explosion hazards as shipped. Small chips, fine turnings, and dust from processing may be readily ignitable.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	Not sensitive.
<b>Sensitivity to static discharge</b>	Not sensitive. Dust from processing Take precautionary measures against static discharges.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Avoid contact with sharp edges or heated metal. Use personal protection recommended in Section 8 of the SDS.
<b>Personal precautions, protective equipment and emergency procedures</b>	
<b>For emergency responders</b>	Avoid contact with sharp edges or heated metal. Use personal protection recommended in Section 8 of the SDS.
<b>Evacuation procedures</b>	None necessary.
<b>Methods and materials for containment and cleaning up</b>	<p>Pick up mechanically. Collect scrap for recycling.</p> <p>If molten: Use dry sand to contain the flow of material. All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Allow the spill to cool before remelting as scrap.</p>
<b>Environmental precautions</b>	No special environmental precautions required.

## 7. Handling and storage

<b>Handling</b>	Avoid generating dust. Avoid contact with sharp edges or heated metal. Hot and cold aluminum are not visually different. Hot aluminum does not necessarily glow red. Use personal protection recommended in Section 8 of the SDS.
<b>Storage</b>	Keep material dry.
<b>Requirements for Processes Which Generate Dusts or Fines</b>	<p>If processing of this product generates dust or if extremely fine particulate is generated, obtain and follow the safety procedures and equipment guides contained in Aluminum Association Bulletin F-1 and National Fire Protection Association (NFPA) standards listed in Section 16.</p> <p>Use non-sparking handling equipment, tools and natural bristle brush. Cover and reseal partially empty containers. Provide grounding and bonding where necessary to prevent accumulation of static charges during metal dust handling and transfer operations (See Section 15).</p> <p>Local ventilation and vacuum systems must be designed to handle explosive dusts. Dry vacuums and electrostatic precipitators must not be used, unless specifically approved for use with flammable/explosive dusts. Dust collection systems must be dedicated to aluminum dust only and should be clearly labeled as such. Do not co-mingle fines of aluminum with fines of iron, iron oxide (rust) or other metal oxides.</p> <p>Do not allow small chunks, fines or dust to contact water, particularly in enclosed areas.</p> <p>Avoid all ignition sources. Good housekeeping practices must be maintained. Do not use compressed air to remove settled material from floors, beams or equipment.</p>

## Requirements for Remelting of Scrap Material or Ingot

Molten metal and water can be an explosive combination. The risk is greatest when there is sufficient molten metal to entrap or seal off the water. Water and other forms of contamination on or contained in scrap or remelt ingot are known to have caused explosions in melting operations. While the products may have minimal surface roughness and internal voids, there remains the possibility of moisture contamination or entrapment. If confined, even a few drops of water can lead to violent explosions.

All tooling, containers, molds and ladles which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Any surfaces that may contact molten metal (e.g., concrete) should be specially coated.

Drops of molten metal in water (e.g. from plasma arc cutting), while not normally an explosion hazard, can generate enough flammable hydrogen gas to present an explosion hazard. Vigorous circulation of the water and removal of the particles minimize the hazards.

During melting operations, the following minimum guidelines should be observed:

- Inspect all materials prior to furnace charging and completely remove surface contamination such as water, ice, snow, deposits of grease and oil or other surface contamination resulting from weather exposure, shipment, or storage.
- Store materials in dry, heated areas with any cracks or cavities pointed downwards.
- Preheat and dry large items adequately before charging into a furnace containing molten metal. This is typically done by use of a drying oven or homogenizing furnace. The drying cycle should bring the metal temperature of the coldest item of the batch to 400°F (200°C) and then hold at that temperature for 6 hours.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA Components

Type	Value	Form
Aluminum (CAS 7429-90-5)	5 mg/m <sup>3</sup>	Respirable fraction
	15 mg/m <sup>3</sup>	Total dust
Chromium (CAS 7440-47-3)	1 mg/m <sup>3</sup>	
Manganese (CAS 7439-96-5)	5 mg/m <sup>3</sup>	Fume

#### Compounds Formed During Processing

Type	Value	Form
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	5 mg/m <sup>3</sup>	Respirable fraction.
	15 mg/m <sup>3</sup>	Total dust.
Chromium (II) compounds	0.5 mg/m <sup>3</sup>	(as Cr)
Chromium (III) compounds	0.5 mg/m <sup>3</sup>	(as Cr)
Chromium (VI) compounds, certain water insoluble forms	0.0025 mg/m <sup>3</sup>	Action Level as Cr(VI))
Chromium (VI) compounds (CAS 18540-29-9)	0.0025 mg/m <sup>3</sup>	Action Level as Cr(VI)
Magnesium oxide (CAS 1309-48-4)	15 mg/m <sup>3</sup>	Total particulate.
Manganese compounds, inorganic	5 mg/m <sup>3</sup>	(as Mn) Fume
Nitric oxide (CAS 10102-43-9)	30 mg/m <sup>3</sup>	
	25 ppm	
Ozone (CAS 10028-15-6)	0.2 mg/m <sup>3</sup>	
	0.1 ppm	
Zinc oxide (CAS 1314-13-2)	5 mg/m <sup>3</sup>	Respirable fraction.
	5 mg/m <sup>3</sup>	Fume.
	15 mg/m <sup>3</sup>	Total dust.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Chromium (VI) compounds, certain water insoluble forms	TWA	0.005 mg/m3	as Cr(VI)
Chromium (VI) compounds, water soluble forms	TWA	0.005 mg/m3	
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.005 mg/m3	as Cr(VI)

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Mineral oil (CAS 8012-95-1)	PEL	5 mg/m3	Mist.
Nitrogen dioxide (CAS 10102-44-0)	Ceiling	9 mg/m3	
		5 ppm	

**ACGIH**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Manganese (CAS 7439-96-5)	TWA (inhalable fraction)	0.2 mg/m3	(inhalable fraction)
	TWA (respirable fraction)	0.02 mg/m3	(respirable fraction)

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction, as Al
Chromium (VI) compounds, water soluble forms	TWA	0.05 mg/m3	(as Cr)
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.05 mg/m3	Soluble compounds as Cr
Ozone (CAS 10028-15-6)	TWA	0.2 ppm	(Heavy, moderate or light workloads (≤2 hours))

**US ACGIH Threshold Limit Values: Short Term Exposure Limit (STEL): mg/m3**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.

**US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3 & ppm**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Nitric oxide (CAS 10102-43-9)	TWA	25 ppm	
Nitrogen dioxide (CAS 10102-44-0)	TWA	0.2 ppm	

**US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Chromium (III) compounds	TWA	0.5 mg/m3	
Chromium (VI) compounds, certain water insoluble forms	TWA	0.01 mg/m3	(as Cr)

**US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.01 mg/m3	Insoluble compounds as Cr
Magnesium oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Manganese compounds, inorganic	TWA	0.1 mg/m3	Inhalable fraction.
Mineral oil (CAS 8012-95-1)	TWA	0.02 mg/m3 5 mg/m3	Respirable fraction. Inhalable fraction.
Zinc oxide (CAS 1314-13-2)	TWA	2 mg/m3	Respirable fraction.

**Alcoa Components**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Aluminum (CAS 7429-90-5)	TWA	3 mg/m3 10 mg/m3	Respirable fraction Total dust
Manganese (CAS 7439-96-5)	TWA	0.05 mg/m3	Total dust.

**Compounds Formed During Processing**

<b>Compounds Formed During Processing</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	TWA	3 mg/m3	Respirable fraction.
Chromium (VI) compounds (CAS 18540-29-9)	TWA	10 mg/m3 0.25 µg/m3	Total dust.
Manganese compounds, inorganic	TWA	0.05 mg/m3 0.02 mg/m3	Total dust, as Mn. Respirable fraction, as Mn.
Mineral oil (CAS 8012-95-1)	TWA	0.5 mg/m3	(8 Hour)

**General**

The need for personal protective equipment should be based upon a hazard assessment and recommendations from health / safety professionals.

If the product is coated with oil, wear oil-resistant gloves to avoid skin contact. Minimize breathing oil vapors and mist. Remove oil contaminated clothing; launder or dry-clean before reuse. Remove oil contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at the end of the work period. Oil coating is readily removed from skin with waterless hand cleaners followed by a thorough washing with soap and water.

**Appropriate engineering controls**

Dust and fumes from processing: Use with adequate explosion-proof ventilation to meet the limits listed in Section 8.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields.

**Skin protection**

**Hand protection**

Wear impervious gloves to avoid repeated or prolonged skin contact with residual oils and to avoid any skin injury.

**Other**

Personnel who handle and work with molten metal should utilize primary protective clothing like polycarbonate face shields, fire resistant tapper's jackets, neck shades (snoods), leggings, spats and similar equipment to prevent burn injuries. In addition to primary protection, secondary or day-to-day work clothing that is fire resistant and sheds metal splash is recommended for use with molten metal. Synthetic materials should never be worn even as secondary clothing (undergarments).

**Respiratory protection**

Dust and fumes from processing: Use NIOSH-approved respiratory protection as specified by an Industrial Hygienist or other qualified professional if concentrations exceed the limits listed in Section 8. Suitable respiratory protective device recommended: P95.

**Thermal hazards**

Contact with molten material can cause thermal burns.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice.

<b>Control parameters</b>	Follow standard monitoring procedures.
<b>Environmental exposure controls</b>	No special environmental precautions required.

## 9. Physical and chemical properties

<b>Form</b>	Solid.
<b>Color</b>	Silvery.
<b>Odor</b>	Odorless
<b>Odor threshold</b>	Not applicable
<b>pH</b>	Not applicable
<b>Density</b>	2.69 - 2.70 g/cm <sup>3</sup> (0.097 - 0.098 lb/in <sup>3</sup> )
<b>Melting point/freezing point</b>	1025 - 1210 °F (551.67 - 654.44 °C)
<b>Initial boiling point and boiling range</b>	Not determined
<b>Flash point</b>	Not applicable
<b>Evaporation rate</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - upper (%)</b>	Not applicable
<b>Flammability limit - lower (%)</b>	Not applicable
<b>Explosive properties</b>	Not applicable.
<b>Vapor pressure</b>	Not applicable
<b>Vapor density</b>	Not applicable
<b>Relative density</b>	Not determined.
<b>Solubility(ies)</b>	Insoluble
<b>Partition coefficient (n-octanol/water)</b>	Not applicable.
<b>Auto-ignition temperature</b>	Not applicable
<b>Decomposition temperature</b>	Not applicable.
<b>Viscosity</b>	Not applicable.

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Stable under normal conditions of use, storage, and transportation as shipped.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Chips, fines, dust and molten metal are considerably more reactive with the following: <ul style="list-style-type: none"> <li>• Water: Slowly generates flammable/explosive hydrogen gas and heat. Generation rate is greatly increased with smaller particles (e.g., fines and dusts). Molten metal can react violently/explosively with water or moisture, particularly when the water is entrapped.</li> <li>• Heat: Oxidizes at a rate dependent upon temperature and particle size.</li> </ul>

## Incompatible materials

Chips, fines, dust and molten metal are considerably more reactive with the following:

- Strong oxidizers: Violent reaction with considerable heat generation. Can react explosively with nitrates (e.g., ammonium nitrate and fertilizers containing nitrate) when heated or molten.
- Acids and alkalis: Reacts to generate flammable/explosive hydrogen gas. Generation rate is greatly increased with smaller particles (e.g., fines and dusts).
- Halogenated compounds: Many halogenated hydrocarbons, including halogenated fire extinguishing agents, can react violently with finely divided or molten aluminum.
- Iron powder and water: Explosive reaction forming hydrogen gas when heated above 1470°F (800°C).
- Iron oxide (rust) and other metal oxides (e.g., copper and lead oxides): A violent thermite reaction generating considerable heat can occur. Reaction with aluminum fines and dusts requires only very weak ignition sources for initiation. Molten aluminum can react violently with iron oxide without external ignition source.

Thermite explosions have been reported when aluminum alloys were melted in furnaces used for alloying with lead, bismuth or other metals with low melting temperatures. These metals, when added as high purity ingots, can seep through cracks in furnace liners and become oxidized. During subsequent melts in the furnace, molten aluminum can contact these metal oxides resulting in a thermite explosion.

## Hazardous decomposition products

No hazardous decomposition products are known.

## 11. Toxicological information

### Health effects associated with ingredients

Aluminum dust/fines and fumes: Low health risk by inhalation. Generally considered to be biologically inert.

Chromium dust and fumes: Can cause irritation of eye, skin and respiratory tract. Metallic chromium and trivalent chromium: Not classifiable as to their carcinogenicity to humans by IARC.

Some products are supplied with an oil coating or have residual oil from the manufacturing process. Oil: Can cause irritation of skin. Skin contact (prolonged or repeated): Can cause dermatitis.



## Health effects associated with compounds formed during processing

The following could be expected if welded, remelted or otherwise processed at elevated temperatures:

Alumina (aluminum oxide): Low health risk by inhalation. Generally considered to be biologically inert.

Zinc oxide fumes: Can cause irritation of upper respiratory tract. Acute overexposures: Can cause metal fume fever (nausea, fever, chills, shortness of breath and malaise).

Manganese oxide fumes: Can cause irritation of the eyes, skin, and respiratory tract. Acute overexposures: Can cause metal fume fever (nausea, fever, chills, shortness of breath and malaise).

Manganese compounds: Chronic overexposures: Can cause inflammation of the lung tissues, scarring of the lungs (pulmonary fibrosis), central nervous system damage, Secondary Parkinson's Disease and reproductive harm in males.

Hexavalent chromium compounds (Chromium VI): Can cause irritation of eye, skin and respiratory tract. Skin contact: Can cause irritant dermatitis, allergic reactions and skin ulcers. Chronic overexposures: Can cause perforation of the nasal septum, respiratory sensitization, asthma, the accumulation of fluid in the lungs (pulmonary edema), lung damage, kidney damage, lung cancer, nasal cancer and cancer of the gastrointestinal tract. IARC/NTP: Listed as "known to be a human carcinogen" by the NTP. Listed as carcinogenic to humans by IARC (Group 1).

If the product is heated well above ambient temperatures or machined, oil vapor or mist may be generated.

Oil vapor or mist: Can cause irritation of respiratory tract. Acute overexposures: Can cause bronchitis, headache, central nervous system effects (nausea, dizziness and loss of coordination) and drowsiness (narcosis).

Welding, plasma arc cutting, and arc spray metalizing can generate ozone.

Ozone: Can cause irritation of eyes, nose and upper respiratory tract. Acute overexposures: Can cause shortness of breath, tightness of chest, headache, cough, nausea and narrowing of airways. Effects are reversible on cessation of exposure. Acute overexposures (high concentrations): Can cause respiratory distress, respiratory tract damage, bleeding and the accumulation of fluid in the lungs (pulmonary edema). Effects can be delayed up to 1-2 hours. Additional information: Studies (inhalation) with experimental animals have found genetic damage, reproductive harm, blood cell damage, lung damage and death.

Welding fumes: IARC/NTP: Listed as possibly carcinogenic to humans by IARC (Group 2B). Additional information: In one study, occupational asthma was associated with exposures to fumes from aluminum welding.

Plasma arc cutting of aluminum can generate oxides of nitrogen.

Oxides of nitrogen (NO and NO<sub>2</sub>): Can cause irritation of eyes, skin and respiratory tract. Acute overexposures: Can cause reduced ability of the blood to carry oxygen (methemoglobin). Can cause cough, shortness of breath, accumulation of fluid in the lungs (pulmonary edema) and death. Effects can be delayed up to 2-3 weeks.

Nitrogen dioxide (NO<sub>2</sub>): Chronic overexposures: Can cause scarring of the lungs (pulmonary fibrosis).

## Information on likely routes of exposure

**Eye contact** Dust and fumes from processing: Can cause irritation.

**Skin contact** Dust and fumes from processing: Can cause irritation.

**Inhalation** Acute overexposure: Can cause metal fume fever (nausea, fever, chills, shortness of breath and malaise), reduced ability of the blood to carry oxygen (methemoglobin) and the accumulation of fluid in the lungs (pulmonary edema). Dust: Can cause irritation of the upper respiratory tract.

Additional health effects from elevated temperature processing (e.g., welding, melting): Fumes: Can cause irritation of the respiratory tract. Chronic overexposures: Can cause respiratory sensitization, scarring of the lungs (pulmonary fibrosis), secondary Parkinson's disease, reproductive harm in males and lung cancer.

**Ingestion** Not relevant, due to the form of the product.

**Symptoms related to the physical, chemical and toxicological characteristics** Dust and fumes from processing: Can cause irritation of the eyes, skin and respiratory tract.

## Information on toxicological effects

Components	Species	Test Results
Aluminum (CAS 7429-90-5)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 2.3 mg/l 7.6 mg/l

Components	Species	Test Results
<b>Oral</b> LD50	Rat	> 2000 mg/kg
Zinc (CAS 7440-66-6)		
<b>Acute</b>		
<b>Oral</b> LD50	Rat	630 mg/kg
<b>Compounds Formed During Processing</b>	<b>Species</b>	<b>Test Results</b>
Aluminum oxide (non-fibrous) (CAS 1344-28-1)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 2.3 mg/l 7.6 mg/l
<b>Oral</b> LD50	Rat	> 5000 mg/kg
Nitric oxide (CAS 10102-43-9)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	115 ppm, 1 Hours 57.5 ppm, 4 Hours
Nitrogen dioxide (CAS 10102-44-0)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Guinea pig Rat	30 ppm, 1 Hours 88 ppm, 4 Hours
Zinc oxide (CAS 1314-13-2)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Mouse	> 5.7 mg/l, 4 Hours
<b>Oral</b> LD50	Mouse Rat	7950 mg/kg > 5000 mg/kg > 5 g/kg
<b>Acute toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.	
<b>Serious eye damage/eye irritation</b>	Based on available data, the classification criteria are not met.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitization</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.	
<b>Pre-existing conditions aggravated by exposure</b>	Dust and fume from processing: Asthma, chronic lung disease, Secondary Parkinson's disease and skin rashes.	
<b>Carcinogenicity</b>	Not classified. Based on available data, the classification criteria are not met.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Chromium (CAS 7440-47-3)	3 Not classifiable as to carcinogenicity to humans.	
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - single exposure</b>	Based on available data, the classification criteria are not met.	

**Specific target organ toxicity - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 12. Ecological information

**Ecotoxicity** No data available for this product.

Components		Species	Test Results
Chromium (CAS 7440-47-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	0.01 - 0.7 mg/l, 48 hours
Fish	LC50	Carp (Cyprinus carpio)	14.3 mg/l, 96 hours
Manganese (CAS 7439-96-5)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	40 mg/l, 48 hours
Zinc (CAS 7440-66-6)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	2.8 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.56 mg/l, 96 hours

Compounds Formed During Processing		Species	Test Results
Nitrogen dioxide (CAS 10102-44-0)			
<b>Aquatic</b>			
Fish	LC50	Tench (Tinca tinca)	19.6 mg/l, 96 hours
Ozone (CAS 10028-15-6)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.0081 - 0.0106 mg/l, 96 hours
Zinc oxide (CAS 1314-13-2)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	2246 mg/l, 96 hours

**Persistence and degradability** The product contains inorganic compounds which are not biodegradable.

**Bioaccumulative potential** The product is not bioaccumulating.

**Mobility in soil** Not considered mobile.

**Other adverse effects** None known.

## 13. Disposal considerations

**Disposal instructions** Reuse or recycle material whenever possible. If reuse or recycling is not possible, disposal must be made according to local or governmental regulations.

**Waste codes** RCRA Status: Not federally regulated in the U.S. if disposed of "as is."

RCRA waste codes other than described here may apply depending on use of the product. Status must be determined at the point of waste generation. Refer to 40 CFR 261 or state equivalent in the U.S. TCLP testing is recommended for chromium in a waste disposal scenario.

**Waste from residues / unused products** If reuse or recycling is not possible, disposal must be made according to local or governmental regulations.

**Contaminated packaging** Dispose of in accordance with local regulations.

## 14. Transport information

### General Shipping Information

#### Basic Shipping Information

<b>ID number</b>	-
<b>Proper shipping name</b>	Not regulated
<b>Hazard class</b>	-
<b>Packing group</b>	-

## General Shipping Notes

- When "Not regulated", enter the proper freight classification, SDS Number and Product Name onto the shipping paperwork.

## Disclaimer

This section provides basic classification information and, where relevant, information with respect to specific modal regulations, environmental hazards and special precautions. Otherwise, it is presumed that the information is not available/not relevant

## 15. Regulatory information

### US federal regulations

In reference to Title VI of the Clean Air Act of 1990, this material does not contain nor was it manufactured using ozone-depleting chemicals.

All electrical equipment must be suitable for use in hazardous atmospheres involving aluminum powder in accordance with 29 CFR 1910.307. The National Electrical Code, NFPA 70, contains guidelines for determining the type and design of equipment and installation which will meet this requirement.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Chromium (CAS 7440-47-3)	Listed.
Manganese (CAS 7439-96-5)	Listed.
Zinc (CAS 7440-66-6)	Listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

<b>Section 311/312 hazard categories</b>	Immediate Hazard - Yes	If particulates/fumes generated during processing
	Delayed Hazard - Yes	If particulates/fumes generated during processing
	Fire Hazard - No	
	Pressure Hazard - No	
	Reactivity Hazard - Yes	If molten

### SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Ozone	10028-15-6	100	100 lbs		
Nitric oxide	10102-43-9	10	100 lbs		
Nitrogen dioxide	10102-44-0	10	100 lbs		

**SARA 311/312 Hazardous chemical** No

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum	7429-90-5	96 - 99
Zinc	7440-66-6	<6.5
Manganese	7439-96-5	<1.5
Manganese compounds, inorganic	Not available	>= 1
Zinc oxide	1314-13-2	>= 1
Chromium (II) compounds	Not available	>= 1
Chromium (III) compounds	Not available	>= 1
Chromium (VI) compounds, water soluble forms	Not available	>= 1
Chromium (VI) compounds	18540-29-9	>= 1
Chromium (VI) compounds, certain water insoluble forms	Not available	>= 1
Ozone	10028-15-6	>= 1

### US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

### US - New Jersey RTK - Substances: Listed substance

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Magnesium (CAS 7439-95-4)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US - Pennsylvania RTK - Hazardous Substances: All compounds of this substance are considered environmental hazards**

Chromium (CAS 7440-47-3)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US - Pennsylvania RTK - Hazardous Substances: Special hazard**

Chromium (CAS 7440-47-3)

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US. Massachusetts RTK - Substance List**

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Magnesium (CAS 7439-95-4)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US. New Jersey Worker and Community Right-to-Know Act**

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US. Pennsylvania RTK - Hazardous Substances**

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Magnesium (CAS 7439-95-4)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Magnesium (CAS 7439-95-4)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US. Rhode Island RTK**

Aluminum (CAS 7429-90-5)  
Chromium (CAS 7440-47-3)  
Manganese (CAS 7439-96-5)  
Zinc (CAS 7440-66-6)

**US. California Proposition 65**

Not Listed.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>SDS Status</b>	<p>May 27, 2015: New format.  February 24, 2012: New format.  January 6, 2009: New format.  October 12, 2005: Reviewed on a periodic basis in accordance with Alcoa policy. Change(s) in Section: 1, 3, 4, 5, 7, 8, 11 and 15.  July 25, 2002: New format.</p> <p>Origination date: July 10, 1989</p> <p>Hazardous Materials Control Committee  Preparer: Jim Perriello, +1-865-977-2051.</p> <p>SDS System Number: 115726</p>
<b>Revision date</b>	May 27, 2015.
<b>Version #</b>	06
<b>Revision Information</b>	<p>Product and Company Identification: Product and Company Identification  Composition / Information on Ingredients: Ingredients  Physical &amp; Chemical Properties: Multiple Properties  Transport Information: Agency Name, Packaging Type, and Transport Mode Selection  Regulatory Information: Safety Phrases  GHS: Classification</p>
<b>Disclaimer</b>	The information in the sheet was written based on the best knowledge and experience currently available.
<b>Other information</b>	<ul style="list-style-type: none"> <li>• Aluminum Association's Bulletin F-1, "Guidelines for Handling Aluminum Fines Generated During Various Aluminum Fabricating Operations." The Aluminum Association, 1525 Wilson Boulevard, Suite 600, Arlington, Virginia 22209, <a href="http://www.aluminum.org">www.aluminum.org</a>.</li> <li>• Aluminum Association, "Guidelines for Handling Molten Aluminum, The Aluminum Association, 1525 Wilson Boulevard, Suite 600, Arlington, Virginia 22209, <a href="http://www.aluminum.org">www.aluminum.org</a>.</li> <li>• NFPA 484, Standard for Combustible Metals (NFPA phone: 800-344-3555)</li> <li>• NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids</li> <li>• NFPA 70, Standard for National Electrical Code (Electrical Equipment, Grounding and Bonding)</li> <li>• NFPA 77, Standard for Static Electricity</li> </ul>

Key/Legend:

ACGIH	American Conference of Governmental Industrial Hygienists
AICS	Australian Inventory of Chemical Substances
CAS	Chemical Abstract Services
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CFR	Code of Federal Regulations
CPR	Cardio-pulmonary Resuscitation
DOT	Department of Transportation
DSL	Domestic Substances List (Canada)
EC	Effective Concentration
ED	Effective Dose
EINECS	European Inventory of Existing Commercial Chemical Substances
ENCS	Japan - Existing and New Chemical Substances
EWG	European Waste Catalogue
EPA	Environmental Protective Agency
IARC	International Agency for Research on Cancer
LC	Lethal Concentration
LD	Lethal Dose
MAK	Maximum Workplace Concentration (Germany) "maximale Arbeitsplatz-Konzentration"
NDSL	Non-Domestic Substances List (Canada)
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration
PIN	Product Identification Number
PMCC	Pensky Marten Closed Cup
RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act
SIMDUT	Système d'Information sur les Matières Dangereuses Utilisées au Travail
STEL	Short Term Exposure Limit
TCLP	Toxic Chemicals Leachate Program
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System
m meter, cm centimeter, mm millimeter, in inch, g gram, kg kilogram, lb pound, µg microgram, ppm parts per million, ft feet	

\*\*\* End of SDS \*\*\*

## Hazard statement

May form combustible dust concentrations in air.

## Precautionary statement

### Prevention

Keep away from heat/sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Prevent dust accumulation to minimize explosion hazard. Observe good industrial hygiene practices.

### Response

Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

### Storage

Store away from incompatible materials.

## Warning

### Supplemental information

**FIRE FIGHTING MEASURES:** This product does not present fire or explosion hazards as shipped. Small chips, fine turnings and dust from processing may be readily ignitable. Use Class D extinguishing agents on fines, dust or molten metal. Use coarse water spray on chips and turnings.

DO NOT USE halogenated extinguishing agents on small chips/fines.

DO NOT USE water in fighting fires around molten metal.

**IN CASE OF SPILL:** If molten: Use dry sand to contain the flow of material. All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Allow the spill to cool before remelting as scrap. Wear appropriate personal protective equipment.

See Alcoa SDS Number 0509.

USA: Chemtrec: +1-703-527-3887 +1-800-424-9300 (24 Hour Emergency Telephone, multiple languages spoken)

Alcoa Inc., 201 Isabella Street, Pittsburgh, PA 15212-5858 United States +1-412-553-4001 (24 Hour Emergency Telephone, English only)  
Alcoa Health and Safety Email: [accmsds@alcoa.com](mailto:accmsds@alcoa.com) Tel: +1-412-553-4649 and Fax: +1-412-553-4822

